

SB12-75 AGM VRLA
12V – 75AH

General Features:

- Designed floating charging service life: 10 years (25°C)
- Sealed and maintenance free operation
- Safety valve installation for explosion proof
- Low self-discharge characteristic
- Wide operating temperature range from 0°C~40°C
- Lead Aluminium calcium Tin alloy high energy, prevent corrosion



Design Life
10 Years



Low Internal
Resistance



High Current
Performance



Fast
Charging



Recyclable
(Pb)

Applications:

Uninterruptible Power Supply (UPS)
Telecom Stations and Power Station


Medical Equipment's
Fire Alarm and Security Systems

DC Power Supply
Emergency Lighting

Physical Specifications:

Nominal Voltage	Nominal Capacity (10HR)	Dimensions				Weight	Internal Resistance (In full charge status)	Standard Terminals
		Length	Width	Height	Total Height			
12V	75AH	260mm	168mm	212mm	218mm	Approx 23.5kg (51.7lbs)	≈5.8 mΩ	T12 (Standard)

Dimensions:



Constant Voltage Discharge:







Rated Capacity	
20 hour rate (3.75A)	78.9AH
10 hour rate (7.5A)	75.0AH
5 hour rate (12.75A)	63.7AH
3 hour rate (18.75A)	56.3AH
1 hour rate (45.0A)	45.0AH
Capacity affected by Temperature	
40°C(104°F)	103%
25°C(77°F)	100%
0°C(32°F)	86%

Cycle Application
1. Limit initial current less than 18.75A.
2. Charge until battery voltage (under charge) reaches 14.1V to 14.4V at 25°C(77°F).
3. Hold at 14.1V to 14.4V until current drop to under 0.45A for at least 3 hours.
4. Temperature compensation coefficient of charging voltage is -30mV/°C.
Standby Service
1. Hold battery across constant voltage source of 13.6 to 13.8 volts with current limit 18.75A continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charge status.
2. Temperature compensation coefficient of charging voltage is -18mV/°C.

Battery Discharge Table:

End Voltage (V)	Minutes (M)				Hours (H)							
	10	15	30	45	1	1.5	2	3	5	8	10	20
Constant Current Discharge Data Sheet (@25°C) Unit: A												
1.60	184	145	83	71	47.7	37.9	32.0	19.7	13.7	9.40	7.89	4.10
1.65	176	138	78	69	46.9	37.1	31.2	19.4	13.4	9.25	7.80	4.06
1.70	168	132	75	66	45.4	36.3	30.4	19.0	13.1	9.09	7.73	4.02
1.75	159	125	71	64	44.7	35.6	29.8	18.6	12.9	8.86	7.65	3.99
1.80	151	120	68	62	43.9	34.8	29.0	18.2	12.5	8.71	7.50	3.94
Constant Power Discharge Data Sheet (@25°C) Unit: W												
1.60	342.67	284.00	175.67	123.17	102.50	74.67	55.83	41.67	26.83	20.33	15.77	8.48
1.65	326.50	270.33	167.33	119.00	100.00	72.83	54.50	40.50	26.33	20.00	15.60	8.42
1.70	310.67	257.50	159.33	115.00	97.33	71.00	53.17	39.67	25.50	19.67	15.47	8.32
1.75	296.00	245.33	151.67	111.00	95.00	69.33	52.00	38.50	25.00	19.17	15.28	8.23
1.80	282.00	233.50	144.67	107.33	92.83	67.67	50.67	37.67	24.33	18.83	15.15	8.17

Performance Characteristic:



Note:

The battery should be charged within 6 months of storage, Otherwise, permanent loss of capacity might occur as a result of sulfation. Above Information is subject to change. For further queries, please contact info@swiftbatteries.com

